

It's not rocket science,
but following these
instructions will make
installing your seat covers
a lot easier.

We promise.

PART:	34307
PRODUCT:	WESTERN STAR STATIONARY PASSENGER'S SEAT WITH NO ARMRESTS
PIECES:	(1) SEAT BACK (1) SEAT BOTTOM



*Basically, you break it, we buy it.
Seriously.*

Your new seat covers are covered by a two-year, unconditional, no B.S. warranty.

That means that if you manage to abuse them to a point that they can't perform like they're supposed to within two years of when you bought them, we'll make it right. Depending on what is more practical, we'll either repair or replace the damaged cover.

General care instructions:

1. In most cases dirt, debris, spills and pet hair can be removed by wiping with a damp cloth.
2. Seat covers can be removed and machine washed on low temperature setting using mild detergent.
Drip dry or machine tumble dry on a no heat cycle.
Straps should be coiled and secured with rubber bands for machine washing and drying.
3. Soil may be removed with spray cleaner or detergent and water.
4. Oil or grease stains should first be treated with a dry cleaning solvent followed by a spray cleaner or detergent and water.
5. Do not use bleach.

Install Seat Cover

SEAT DOES NOT NEED TO BE REMOVED TO INSTALL COVER.

Turn seat cover partly inside out.

Begin working down seat back.



Push flap between the seat back and bottom.

Push flaps between the seat back and bottom.



Fold seat bottom open again. Secure the velcro tabs on the side.

Pull velcro tab at the bottom tight and secure.

From the back of the seat, pull flaps tight and secure to velcro.



FINISHED.

Pull the seat bottom up to open the compartment.

Slide the cover over making sure the seams line up with the edges of the seat.

